



SAFETY DATA SHEET

1. Product and company identification

Product name Bel-Ray EXS Synthetic Ester 4T Engine Oil 5W-40
Product code 99150
SDS number 6631

Bel-Ray Company, LLC
PO Box 526
Farmingdale, New Jersey USA 07727
1 732-938-2421
CHEMTREC: 1800 069 100 (AUS)

Bel-Ray Company, LLC
P.O. Box 526
Farmingdale, NJ 07727
United States of America
+1 732 938 2421
CHEMTREC: 800-424-9300 (USA)
CHEMTREC: +1 703-527-3887 (outside USA - call collect)

Recommended use and Limitations on use

Not available.

2. Hazards identification

GHS classification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity following single exposure	Category 3 respiratory tract irritation
Environmental hazards	Not classified.	

Label elements

Symbols None.

Signal word None.

Hazard statement Causes skin irritation. Causes serious eye irritation. Causes serious eye irritation. Toxic if inhaled. May cause respiratory irritation. Suspected of causing genetic defects. May cause damage to organs (). Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

Precautionary statement

Prevention Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapour. Wash thoroughly after handling. Avoid release to the environment. Wear eye/face protection. Wear protective gloves. Use personal protective equipment as required.

Response If medical advice is needed, have product container or label at hand. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTRE or doctor/physician. Specific treatment (see on this label). If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Substance or mixture Mixture

Chemical property	CAS Number	Concentration (%)
Hydrogenated Polydecene	68037-01-4	40 - < 50

	CAS Number	Concentration (%)
Paraffin oils (petroleum), catalytic de-waxed light Paraffin Oils (petroleum), Catalytic Dewaxed Light	64742-71-8	0 - < 20
White mineral oil (petroleum) White Mineral Oil (petroleum)	8042-47-5	0 - < 20
Decanoic acid, Ester With 2-ethyl-2-(hydroxymethyl)-1,3-propanediol Octanoate Decanoic Acid, Ester With 2-ethyl-2-(hydroxymethyl)-1,3-propanediol Octanoate	11138-60-6	5 - < 10
Zinc, Dithiophosphate Di-c1-14-alkyl Esters	68649-42-3	< 1
Other components below reportable levels		40 - < 50

4. First aid measures

Inhalation	Move to fresh air. Call a POISON CENTRE or doctor/physician.
Skin contact	Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a POISON CENTRE or doctor/physician if you feel unwell. Rinse mouth. Do not induce vomiting. Never give liquid to an unconscious person.
Potential delayed effects	Not available.
Personal protection for first-aid responders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.
Notes to physician	Not available.

5. Fire-fighting measures

Extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Extinguishing media to avoid	Do not use water jet as an extinguisher, as this will spread the fire. Water.
HAZCHEM Code Number	None.
Specific hazards during fire fighting	None.
Special fire fighting procedures	None.
Protection of fire-fighters	Water runoff can cause environmental damage.
Hazards from combustion products	May include oxides of Nitrogen. Carbon monoxide and carbon dioxide.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Immediately evacuate personnel to safe areas. Local authorities should be advised if significant spillages cannot be contained. Do not touch or walk through spilled material. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. In case of spills, beware of slippery floors and surfaces.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.
Spill cleanup methods	<p>This product is miscible in water.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Prevent product from entering drains.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills in original containers for re-use. For waste disposal, see section 13.</p>

7. Handling and storage

Handling

Precautions	Obtain special instructions before use. Use personal protective equipment as required. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.
Safe handling advice	Do not handle until all safety precautions have been read and understood. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use personal protection recommended in Section 8 of the MSDS.
Prevention of fire and explosion	No specific recommendations.

Storage

Suitable storage conditions	Store locked up. Room temperature - normal conditions. Keep container tightly closed. Keep out of the reach of children.
Incompatible materials	None known.
Safe packaging materials	Keep in original container.

8. Exposure controls/personal protection

Exposure limits

New Zealand. WES. (Workplace Exposure Standards)

Components	Type	Value	Form
Paraffin oils (petroleum), catalytic de-waxed light (64742-71-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
White mineral oil (petroleum) (8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Paraffin oils (petroleum), catalytic de-waxed light (64742-71-8)	TWA	5 mg/m3	Inhalable fraction.
White mineral oil (petroleum) (8042-47-5)	TWA	5 mg/m3	Inhalable fraction.

Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)

Components	Type	Value	Form
Paraffin oils (petroleum), catalytic de-waxed light (64742-71-8)	TWA	5 mg/m3	Mist.
White mineral oil (petroleum) (8042-47-5)	TWA	5 mg/m3	Mist.

Engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide adequate general and local exhaust ventilation.
-----------------------------	---

Personal protective equipment

Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Skin protection	Wear suitable protective clothing. Wear protective gloves.
Eye/face protection	Wear eye/face protection.
Radioactive or thermal hazards	Not available.
Hygiene measures	Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practices.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid. Liquid.

Colour	Amber. Amber.
Odour	Petroleum Petroleum
pH	Not available.
Odour threshold	Not available.
Melting point/freezing point	Not available.
Boiling point, Initial boiling point, and boiling range	> 250 °C (> 482 °F)
Flash point	194.00 °C (381.20 °F) Pensky-Martens Closed Cup
Auto-ignition temperature	260 °C (500 °F) estimated
Flammability (solid, gas)	Not available.
Flammability limit - lower (%)	1 % estimated
Flammability limit - upper (%)	50 % estimated
Explosive limit	Not available.
Vapour pressure	0.000011004 hPa estimated
Density	856.00 kg/m ³
Vapour density	Not available.
Evaporation rate	Not available.
Relative density	Not available.
Solubility	Negligible
Solubility (other)	Hydrocarbon Solvents Oil
Partition coefficient (n-octanol/water)	Not available.
Decomposition temperature	Not available.
Viscosity	85.05 cSt ASTM D445
Percent volatile	0.051997542 % estimated
Other data	
Flammability class	Combustible IIIB estimated
Specific gravity	0.856
Viscosity temperature	40 °C (104 °F)
VOC (Weight %)	0.051997542 % estimated

10. Stability and reactivity

Stability	Material is stable under normal conditions.
Conditions to avoid	Avoid temperatures exceeding the flash point.
Incompatible materials	None known.
Hazardous decomposition products	Nitrogen oxides (NO _x). At thermal decomposition temperatures, carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

11. Toxicological information

Acute toxicity	Toxic by inhalation.	
Product	Species	Test results
Bel-Ray EXS Synthetic Ester 4T Engine Oil 5W-40 (Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	32475.1777 mg/kg, estimated
<i>Inhalation</i>		
LC50	Rat	1005.532 mg/l, estimated

Product	Species	Test results
<i>Oral</i> LD50	Rat	11928.1563 mg/kg, estimated 1923.1232 g/kg, estimated

* Estimates for product may be based on additional component data not shown.

Routes of exposure	Inhalation. Skin contact. Eye contact.
Symptoms	Discomfort in the chest. Shortness of breath. Coughing. Irritant effects.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory sensitiser	Due to lack of data the classification is not possible.
Skin sensitiser	Due to lack of data the classification is not possible.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Due to lack of data the classification is not possible.
Toxic to reproduction	Due to lack of data the classification is not possible.
Specific target organ toxicity - single exposure	Respiratory tract irritation.
Specific target organ toxicity - repeated exposure	Due to lack of data the classification is not possible.
Aspiration hazard	Due to lack of data the classification is not possible.
Chronic effects	Prolonged inhalation may be harmful.
Relevant negative data	Not available.

12. Ecological information

Ecotoxicological data

Product	Species	Test results
Bel-Ray EXS Synthetic Ester 4T Engine Oil 5W-40 (Mixture)		
Crustacea	EC50	Daphnia
		942.3303 mg/l, 48 hours, estimated
Fish	LC50	Fish
		3337.5801 mg/l, 96 hours, estimated

* Estimates for product may be based on additional component data not shown.

Ecotoxicity	Accumulation in aquatic organisms is expected. Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulation	Not available.
Mobility	This product is miscible in water.
Other hazardous effects	Not available.

13. Disposal considerations

Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Not available.

14. Transport information

International regulations

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

Applicable regulations

New Zealand Inventory of Chemicals (NZIoC): Registration status

Decanoic acid, Ester With 2-ethyl-2-(hydroxymethyl)-1,3-propanediol Octanoate (CAS 11138-60-6)	May be used as a single component chemical under an appropriate group standard
Hydrogenated Polydecene (CAS 68037-01-4)	May be used as a single component chemical under an appropriate group standard
Paraffin oils (petroleum), catalytic de-waxed light (CAS 64742-71-8)	May be used as a component in a product covered by a group standard but it is not approved for use as a chemical in its own right.
White mineral oil (petroleum) (CAS 8042-47-5)	May be used as a single component chemical under an appropriate group standard
Zinc, Dithiophosphate Di-c1-14-alkyl Esters (CAS 68649-42-3)	May be used as a component in a product covered by a group standard but it is not approved for use as a chemical in its own right.

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

References Not available.

Issued by
Not available.

Prepared by
Not available.

Disclaimer Bel-Ray Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

Issue date 13-January-2011

Revision date 29-July-2014