



SAFETY DATA SHEET

1. Product and company identification

Product name Bel-Ray 6 in 1
Product code 99020
SDS number 6896

Bel-Ray Company, LLC
GPO Box 2650 Sydney, NSW 1171
PO Box 526 Farmingdale N.J. 07727
1 732-938-2421
CHEMTREC: 1800 069 100 (AUS)

Bel-Ray Company, LLC
P.O. Box 526
Farmingdale, NJ 07727
United States of America
+1 732 938 2421
CHEMTREC: 800-424-9300 (USA)
CHEMTREC: +1 703-527-3887 (outside USA - call collect)

Recommended use and Limitations on use

Recommended use Lubricant

2. Hazards identification

GHS classification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, dermal	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Reproductive toxicity	Category 1
	Specific target organ toxicity following single exposure	Category 3 narcotic effects
	Specific target organ toxicity following repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 3

Label elements

Symbols



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Causes skin irritation. May cause an allergic skin reaction. Causes eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use. Do not breathe mist or vapour. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves. Use personal protective equipment as required.

Response

If medical advice is needed, have product container or label at hand. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or if you feel unwell: Call a POISON CENTRE or doctor/physician. Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information

None.

3. Composition/information on ingredients

Substance or mixture Mixture

Chemical property	CAS Number	Concentration (%)
Hydrotreated Light Distillates (petroleum)	64742-47-8	20 - < 40
Stoddard solvent Stoddard Solvent	8052-41-3	10 - < 20
Carbon dioxide Carbon Dioxide	124-38-9	3 - < 5
2-Butoxyethanol 2-butoxyethanol	111-76-2	1 - < 2
Tris(methylphenyl) Phosphate	1330-78-5	< 1
Butylhydroxytoluene	128-37-0	< 0.3
Other components below reportable levels		30 - < 40

4. First aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Never give liquid to an unconscious person.

Potential delayed effects

Diarrhoea. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Personal protection for first-aid responders

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

Notes to physician

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Extinguishing media

Alcohol resistant foam. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Extinguishing media to avoid

Do not use water jet as an extinguisher, as this will spread the fire.

HAZCHEM Code Number	None.
Specific hazards during fire fighting	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Protection of fire-fighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Hazards from combustion products	Carbon monoxide and carbon dioxide.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
Spill cleanup methods	Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil etc) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapours or divert vapour cloud drift. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Handling	
Precautions	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not breathe mist or vapour. Do not get in eyes, on skin, or on clothing. Pregnant or breastfeeding women must not handle this product. When using, do not eat, drink or smoke. Avoid release to the environment. Do not re-use empty containers.
Safe handling advice	Avoid prolonged exposure. Should be handled in closed systems, if possible. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Use personal protection recommended in Section 8 of the SDS.
Prevention of fire and explosion	Pressurised container: Do not pierce or burn, even after use. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material.
Local and general ventilation	Provide adequate ventilation.
Storage	
Suitable storage conditions	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not handle or store near an open flame, heat or other sources of ignition. Refrigeration recommended. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).
Incompatible materials	Strong oxidising agents. For further information, please refer to section 10.
Safe packaging materials	Pressurised container: Do not pierce or burn, even after use. Ground and bond containers when transferring material. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not use if spray button is missing or defective. Store in original tightly closed container. Do not re-use empty containers.

8. Exposure controls/personal protection

Exposure limits

New Zealand. WES. (Workplace Exposure Standards)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	121 mg/m3
Butylhydroxytoluene (CAS 128-37-0)	TWA	25 ppm 10 mg/m3
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
	TWA	30000 ppm 9000 mg/m3 5000 ppm
Stoddard solvent (CAS 8052-41-3)	TWA	525 mg/m3 100 ppm

ACGIH

Components	Type	Value	Form
Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)	TWA	200 mg/m3	As Total Hydrocarbon Vapor.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	Inhalable fraction and vapor.
Butylhydroxytoluene (CAS 128-37-0)	TWA	2 mg/m3	
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	STEL	246 mg/m3
	TWA	50 ppm 123 mg/m3 25 ppm
Butylhydroxytoluene (CAS 128-37-0)	TWA	10 mg/m3
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3
	TWA	15000 ppm 9150 mg/m3 5000 ppm

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	STEL	242 mg/m3
	TWA	50 ppm 96.9 mg/m3 20 ppm
Butylhydroxytoluene (CAS 128-37-0)	TWA	10 mg/m3
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
	TWA	30000 ppm 22500 mg/m3 12500 ppm

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)

Components	Type	Value
Stoddard solvent (CAS 8052-41-3)	TWA	790 mg/m3
Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)		
Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	STEL	242 mg/m3
	TWA	50 ppm 96.9 mg/m3 20 ppm 10 mg/m3
Butylhydroxytoluene (CAS 128-37-0)	TWA	10 mg/m3
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
	TWA	30000 ppm 22500 mg/m3 12500 ppm 790 mg/m3
Stoddard solvent (CAS 8052-41-3)	TWA	790 mg/m3

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

New Zealand WES: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Skin absorption can be significant.

Engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Personal protective equipment

Respiratory protection

Chemical respirator with organic vapour cartridge and full facepiece.

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

Radioactive or thermal hazards

Follow standard monitoring procedures.

Hygiene measures

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol
Colour	Not available.

Odour Not available.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Boiling point, initial boiling point, and boiling range > 159 °C (> 318.2 °F)

Flash point	43.0 °C (109.4 °F) Pensky-Martens Closed Cup
Auto-ignition temperature	Not available.
Flammability (solid, gas)	Not available.
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	6 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
Vapour pressure	Not available.
Density	820.00 kg/m3
Vapour density	Not available.
Evaporation rate	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Decomposition temperature	Not available.
Viscosity	3 cSt
Viscosity temperature	40 °C (104 °F)
Other data	
Flash point class	Flammable IA
Specific gravity	0.82
VOC	22 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Stability	Risk of ignition.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidising agents.
Hazardous decomposition products	At thermal decomposition temperatures, carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Causes eye irritation.
Acute toxicity	Narcotic effects. May cause an allergic skin reaction.

Product	Species	Test results
Bel-Ray 6 in 1		
<u>Acute</u>		
Dermal		
LD50	Rabbit	26818 ml/kg estimated 10320 mg/kg estimated

Product	Species	Test results
Inhalation LC50	Rat	50000 g/kg estimated
	Mouse	18041 ppm, 7 Hours estimated
	Rat	11598 ppm, 4 Hours estimated
		2213 mg/l estimated
Oral LD50	Guinea pig	31 g/kg estimated
	Mouse	31 g/kg estimated
	Rabbit	8.2 g/kg estimated
	Rat	19667 mg/kg estimated
Components	Species	Test results

2-Butoxyethanol (CAS 111-76-2)

Acute

Dermal

LD50 Rabbit 400 mg/kg

Inhalation

LC50 Mouse 700 ppm, 7 Hours
Rat 450 ppm, 4 Hours

Oral

LD50 Guinea pig 1.2 g/kg
Mouse 1.2 g/kg
Rabbit 0.32 g/kg
Rat 560 mg/kg

Butylhydroxytoluene (CAS 128-37-0)

Acute

Oral

LD50 Guinea pig 10700 mg/kg
Mouse 1040 mg/kg
Rat 890 mg/kg

* Estimates for product may be based on additional component data not shown.

Routes of exposure	Inhalation. Skin contact. Eye contact.
Symptoms	Diarrhoea. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes eye irritation.
Respiratory sensitiser	Based on available data, the classification criteria are not met.
Skin sensitiser	May cause an allergic skin reaction.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
IARC Monographs. Overall Evaluation of Carcinogenicity	
2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
BUTYLATED HYDROXYTOLUENE (BHT) (CAS 128-37-0)	3 Not classifiable as to carcinogenicity to humans.
PETROLEUM SOLVENTS (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
Toxic to reproduction	May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	May cause damage to organs. May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard	Not an aspiration hazard.
Chronic effects	May be harmful if absorbed through skin. Prolonged inhalation may be harmful. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Causes damage to organs through prolonged or repeated exposure.
Relevant negative data	Not available.

12. Ecological information

Ecotoxicological data

Product		Species	Test results
Bel-Ray 6 in 1			
Aquatic			
Crustacea	EC50	Daphnia	165.4532 mg/l, 48 hours estimated
Fish	LC50	Fish	7.5806 mg/l, 96 hours estimated
Components		Species	Test results
2-Butoxyethanol (CAS 111-76-2)			
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Butylhydroxytoluene (CAS 128-37-0)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	1.44 mg/l, 48 hours
Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Tris(methylphenyl) Phosphate (CAS 1330-78-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	2.3 - 4.5 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.21 - 0.32 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Ecotoxicity	Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulation	No data available.
Partition coefficient n-octanol/water (log Kow)	
2-Butoxyethanol	0.83
Stoddard solvent	3.16 - 7.15
Tris(methylphenyl) Phosphate	5.11
Bioconcentration factor (BCF)	Not available.
Mobility	No data available for this product.
Other hazardous effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

14. Transport information

IATA	
UN number	UN1950

Material name: Bel-Ray 6 in 1

99020 Version No.: 6.0 Revision date: 31-May-2016 Print date: 01-June-2016

SDS NEW ZEALAND

8 / 10

UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	5F
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

IATA



15. Regulatory information

Applicable regulations

New Zealand Inventory of Chemicals (NZIoC): Registration status

2-Butoxyethanol (CAS 111-76-2)	HSNO Approved
Butylhydroxytoluene (CAS 128-37-0)	HSNO Approved
Carbon dioxide (CAS 124-38-9)	HSNO Approved
Hydrotreated Light Distillates (petroleum) (CAS 64742-47-8)	May be used as a single component chemical under an appropriate group standard
Stoddard solvent (CAS 8052-41-3)	HSNO Approved
Tris(methylphenyl) Phosphate (CAS 1330-78-5)	HSNO Approved

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no) *
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No

Country(s) or region	Inventory name	On inventory (yes/no) *
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

References	Not available.
Issued by	Not available.
Prepared by	Not available.
Disclaimer	Bel-Ray Company, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Issue date	21-December-2010
Revision date	01-June-2016
Revision information	This document has undergone significant changes and should be reviewed in its entirety.