SPECTRO LUBRICANT TECHNICAL DATA

Golden Semi-Synthetic Engine Oil



- EXCEPTIONALLY HIGH ANTI-WEAR ADDITIVE TREATMENT REDUCES WEAR.
- EXTENDS COMPONENT LIFE.
- TREMENDOUS LUBRICATION PROTECTION IN EXTREME HEAT CONDITIONS.
- PROVIDES LOWER CONSUMPTION RATE.
- EXCEPTIONAL OFF-SEASON PROTECTION OF INTERNAL PARTS.
- API SL JASO MA/MA2

Description

Spectro Golden Semi-Synthetic is the ultimate semi-synthetic motor lubricant formulated specifically for use in high output, high performance engines. It incorporates a blend of the world's leading group IV synthetic base oils and superior quality petroleum base oils with the most advanced anti-wear additive system available for motorcycles.

Application

Golden Semi-Synthetic should be used according to the manufacturer's recommended change intervals and viscosity. If in doubt, use the 10w40. No special steps need to be taken when switching to a semi-synthetic product.

Typical Inspections Kinematic Viscosity @ 100° C cSt Kinematic Viscosity @ 40° C cSt Flash Point, °C Pourpoint, °C Viscosity Index		10w40 15.3 97.2 216 -27 161	20w50 19.6 155.0 230 -23 146
		10w30	15w50
Kinematic Viscosity @ 100° C cSt		11.5	20.2
Kinematic Viscosity @ 40° C cSt		79.5	138
Flash Point, °C		160	245
Pourpoint, °C		-31	-30
Viscosity Index		162	151
Code	Description		Weight
L.GS41030	12/1 Liter Bottles		25 Lbs.
L.GS41040	12/1 Liter Bottles		25 Lbs.
L.GS41550	12/1 Liter Bottles		25 Lbs.
L.GS42050	12/1 Liter Bottles		25 Lbs.
U.GS41030	4/4 Liter Bottles		36 Lbs.
U.GS41040	4/4 Liter Bottles		36 Lbs.
U.GS42050	4/4 Liter Bottles		36 Lbs.
Z.1040SYN	55 gal drum		450 Lbs.
Z.2050SYN	55 gal drum		450 Lbs.

SPECTRO OILS OF AMERICA 993 Federal Rd., Brookfield, CT 06804 203-775-1291 Fax 203-775-8720 www.spectro-oils.com

