

SPECTRO LUBRICANT TECHNICAL DATA

Spectro Diesel-Guard® Super Premium Engine Oil



Description

Diesel-Guard is the ultimate motor lubricant formulated specifically for use in high-performance diesel and gasoline engines. It incorporates the most advanced diesel additive technology available at the highest treat levels.

Meets all known OEM warranty requirements.

Application

Formulated for use in all turbocharged and high load conditions.

Typical Inspections

	15w40
Kinematic Viscosity @ 100° C cST	14.4
Kinematic Viscosity @ 40° C cST	103.0
Flash Point, °C	270
Pourpoint, °C	-28
Sulfated Ash Weight @	0.83
TBN	7.8

Code

R.DG1540
W.DG1540
Z.DG1540

Description

12/1 Quart Bottles
1/5 Gallon Pail
1/55 Gallon Drum

Weight

25 Lbs.
35 Lbs.
450 Lbs

- EXCEPTIONALLY HIGH ANTI-WEAR ADDITIVE TREATMENT REDUCES WEAR.
- BALANCED SOOT DISPERSION AND WEAR CONTROL.
- RESISTANCE TO OXIDATION AND THERMAL BREAKDOWN.
- MEETS API CI-4 AND SL.
- MEETS EUROPEAN CLMC-D1, CCMC-D2, CCMC-GD AND ACEA E5-99.
- MEETS VOLVO VDS-2, VDS-3.
- MEETS CUMMINS 20078
- MEETS MACK EO-M PLUS.

SPECTRO OILS OF AMERICA
993 Federal Rd., Brookfield, CT 06804
203-775-1291 Fax 203-775-8720
www.spectro-oils.com

