

SPECTRO LUBRICANT TECHNICAL DATA

Spectro 2T Engine Lubricant



Description

Spectro 2T is a premium quality two stroke engine lubricant Formulated with high density petroleum base stocks and our Exclusive additives to give exceptionally high levels of Protection and clean operation at all temperatures while guarding against rust and corrosion during long periods of storage.

Application

Spectro 2T is recommended in all two cycle motorcycles and scooters with injection systems. For pre-mix use, a ratio of 32:1 is optimum. (4 oz. per gallon of fuel)

Typical Inspections

Kinematic Viscosity @ 100° C cST	9.4
Kinematic Viscosity @ 40° C cST	77.1
Flash Point, °C	165
Pourpoint, °C	0
Color	Red

Code

L.2T
Z.2T

Description

12/1 Liter Bottles
1/55 Gallon Drum

Weight

25 Lbs.
450 Lbs.

- MINIMIZES SPARK PLUG FOULING
- CONTAINS LOW SMOKE ADDITIVES.
- REDUCES EXHAUST OUTLET DEPOSITS.
- GUARDS AGAINST PISTON SEIZURE.
- EXCEPTIONAL OFF-SEASON PROTECTION OF INTERNAL PARTS.
- API TC & JASO FB QUALITY

SPECTRO OILS OF AMERICA
993 Federal Rd., Brookfield, CT 06804
203-775-1291 Fax 203-775-8720
www.spectro-oils.com

