

SPECTRO LUBRICANT TECHNICAL DATA

Heavy Duty Platinum Full-Synthetic Engine Oil



Description

Heavy Duty Platinum Full Synthetic is engineered specifically for use in Harley® high-performance engines and other high-output V-Twin motors. Spectro Heavy Duty Platinum Full Synthetic's Group IV PAO base stock provides smoother shifting, reduces friction, offers tremendous lubrication and provides superior protection in extreme heat conditions. HD Platinum combines with the most advanced anti-wear additive system available to reduce wear, extend component life, and eliminate valve sticking. A.P.I. SF/SG – Diesel-rated.

Meets all known OEM warranty requirements.

Application

Spectro Heavy Duty oils should be used according to the manufacturer's recommended change intervals and viscosity. They may be used in all Harley® engines, any year, without restriction, and will not void and factory warranty

Typical Inspections **Platinum 20w50**

Kinematic Viscosity @ 100° C cSt	19.6
Kinematic Viscosity @ 0° C cSt	155.0
Flash Point, °C	230
Pourpoint, °C	-23
Viscosity Index	146

- GROUP IV PAO SYNTHETICS THE ULTIMATE LONG-LIFE LUBRICANT.
- EXCEPTIONALLY HIGH ANTI-WEAR ADDITIVE TREATMENT REDUCES WEAR.
- EXTENDS COMPONENT LIFE.
- TREMENDOUS LUBRICATION PROTECTION IN EXTREME HEAT CONDITIONS.
- PROVIDES LOWER CONSUMPTION RATE.
- EXCEPTIONAL OFF-SEASON PROTECTION OF INTERNAL PARTS.
- API SF/SG - CD/CG

Code	Description	Weight
R.HDP25	12/1 quart bottles/case	25 lbs
Z.HDP25	55 gal drum	450 lbs

SPECTRO OILS OF AMERICA
993 Federal Rd., Brookfield, CT 06804
203-775-1291 Fax 203-775-8720
www.spectro-oils.com

